

BESEN PORTABLE EV CHARGER

High power with LCD screen (6A-40A)




BS-PCD040



CEE plug



GB/T



LCD



LED

Model BS-PCD040

Input & Output

Input voltage/Output voltage	100~250V AC
Input frequency	47~63Hz
Max. output power	7.2KW
Max. output current	32A 1Phase
Charging interface type	GB/T

Protection

Over voltage protection	✓
Under voltage protection	✓
Over load protection	✓
Short circuit protection	✓
Earth leakage protection	✓
Over-temp protection	✓
Lightning protection	✓

Function

Ethernet/WIFI/4G/Bluetooth	No
LCD	1.8-inch color display
RCD	Type A
LED Indicator light	Blink (040)
Current adjusting	✓

Working environment

IP rating	IP66
Environment temperature	-40°C ~ +75°C
Relative humidity	0-95% non-condensing
Maximum altitude	<2000m
Cooling	Natural air cooling
Standby power consumption	<8W

Mechanical

Dimension (L/W/D)	265/105/55mm
Weight	5KG

Certificate

Certificate	CE, FCC, RoHS
-------------	---------------

PRODUCT ADVANTAGES

- Higher power for a faster charging speed, max. 32amp
- Large LCD to show real-time current, voltage and time etc.
- Safe use when working at a higher power with built-in intelligent chip